

Data sheet
RATIO®-radio bus system
Repeater 1-Level UPR230/01



The Ratio® repeater 1-Level UPR230/01 serves for the amplification of the radio telegram between Ratio® radio senders and Ratio®-receivers. It is used in case of range difficulties between Ratio®-radio senders and Ratio® receivers.

The Ratio®-UP-Repeater has to be connected to power supply. There is no need to learn in devices. All received telegrams will be transmitted.

Technical Data	Repeater 1-Level UPR230/01	Remarks
Functions	Receiving and strengthened sent of valid radiograms	
Radio technology	Protocol EnOcean, Frequency 868,3MHz Transmission power max. 10mW EIRP Modulation ASK	
Operating data	Rated voltage 230V 50/60Hz Idle current consumption ca. 20mA Power Input ca. 4VA	Rated current 0,5A Power input ca. 25mA Power loss ca. 0,9W
Security	By external automatic cotout 13A Typ C	
Serving and display elements	1 LED shows communication	
Connection	Screw clamp 2,5mm2	
Mechanical Data	Casing: plastic Lexan, Weight: 80g	Dimensions: D=51mm H=25mm
Mounting / Assembly/ Installation	Flush or surface mounting	e.g. behind a socket or in a synthetic casing
Environmental conditions	Environmental temperature in operation -20°C ... +40°C Storage temperature -40°C ... +85°C Relative humidity (non-condensing) 5 ... 90%	
Protection category	IP20 after EN 60529	
Norm conforming assembly	Device conforms to EN 090-2-2 and EN 60669-2-1	
Approbation	R&TTE guidelines 1999/5/EC and conforming to EU guidelines.	
Labeling	According to EMV guidelines (residential and functional buildings), low voltage guideline. ROHS conforming according to 2002/95/EC.	

Safety references
The installation of this equipment may take place only via proven technical personnel. Before working on the equipment the current supply must be switched off. The valid safety and rules for the prevention of accidents are to be considered compellingly.
Area of application
The equipment may only <ul style="list-style-type: none"> To be used for the regulation-moderate employment To be installed firmly in a dry and clean environment To be installed in such a way that an access is possible only with a tool

Diagram of connections	Designation	Typ	Article number
<p>The diagram shows a box labeled 'UPR230/01 1-Level'. Two terminals on the box are labeled 'L' and 'N'. Lines connect these terminals to external 'L' and 'N' labels, representing the power supply connection.</p>	Repeater 1-Level, Supply voltage 230VAC	UPR230/01	9001000